



# Specifications

**Linksys** | SE-Series

## English

---

### Linksys SE1500

|              |                          |
|--------------|--------------------------|
| Model Name   | Linksys SE1500           |
| Model Number | E1000                    |
| Standards    | 802.3, 802.3u            |
| Ports        | Power, Ethernet (1-5)    |
| Buttons      | Power (for EU only), LED |
| LEDs         | Ethernet (1-5), Power    |
| Cabling Type | CAT 5e                   |

#### Environmental

|                    |  |
|--------------------|--|
| Dimensions         | 6.06" x 1.14" x 4.29"<br>(154 x 29 x 109 mm) |
| Unit Weight        | 5.47 oz (155 g)                              |
| Power              | 12V, 0.5A                                    |
| Certifications     | FCC, CE, IC, UL                              |
| Operating Temp.    | 32 to 104°F (0 to 40°C)                      |
| Storage Temp.      | -4 to 140°F (-20 to 60°C)                    |
| Operating Humidity | 10 to 85% Non-condensing                     |
| Storage Humidity   | 5 to 90% Non-condensing                      |

### Linksys SE2500

|              |                                   |
|--------------|-----------------------------------|
| Model Name   | Linksys SE2500                    |
| Model Number | SE2500                            |
| Standards    | 802.3, 802.3u, 802.3x,<br>802.3ab |
| Ports        | Power, Ethernet (1-5)             |
| Buttons      | Power (for EU only), LED          |
| LEDs         | Ethernet (1-5), Power             |
| Cabling Type | CAT 5e                            |

#### Environmental

|                    |  |
|--------------------|--|
| Dimensions         | 6.06" x 1.14" x 4.29"<br>(154 x 29 x 109 mm) |
| Unit Weight        | 5.82 oz (165 g)                              |
| Power              | 12V, 0.5A                                    |
| Certifications     | FCC, CE, IC, UL                              |
| Operating Temp.    | 32 to 104°F (0 to 40°C)                      |
| Storage Temp.      | -4 to 140°F (-20 to 60°C)                    |
| Operating Humidity | 10 to 85% Non-condensing                     |
| Storage Humidity   | 5 to 90% Non-condensing                      |

## Linksys SE2800

|              |                                   |
|--------------|-----------------------------------|
| Model Name   | Linksys SE2800                    |
| Model Number | SE2800                            |
| Standards    | 802.3, 802.3u, 802.3x,<br>802.3ab |
| Ports        | Power, Ethernet (1-8)             |
| Buttons      | Power (for EU only), LED          |
| LEDs         | Ethernet (1-8), Power             |
| Cabling Type | CAT 5eS                           |

### Environmental

|                    |  |
|--------------------|--|
| Dimensions         | 7.56" x 1.18" x 5.83"<br>(192 x 30 x 148 mm) |
| Unit Weight        | 10.23 oz (290 g)                             |
| Power              | 12V, 1A                                      |
| Certifications     | FCC, CE, IC, UL                              |
| Operating Temp.    | 32 to 104°F (0 to 40°C)                      |
| Storage Temp.      | -4 to 140°F (-20 to 60°C)                    |
| Operating Humidity | 10 to 85% Non-condensing                     |
| Storage Humidity   | 5 to 90% Non-condensing                      |

Specifications are subject to change without notice.