

## Linksys 1080p 3MP Indoor Night Vision Dome Camera



LCAD03FLN

### Key Features

- Larger image sensor for better, cleaner images
- ePTZ functionality
- Motion detection
- Audio detection
- Wide dynamic range (WDR)\*
- Privacy mask
- User management
- Profile management
- Event management
- Wide-angle viewing\*
- Image cropping
- ONVIF-compliant v1.0 and v2.0
- Multi-streaming
- True day/night with removable IR-cut filter
- Built-in SD/SDHC card slot for uninterrupted recording
- DI/DO for external sensor and alarm
- POE IEEE 802.3af-compliant
- Video Surveillance Manager software

\* Via firmware upgrade

**Protect your business and enhance your situational awareness with the Linksys 1080p 3MP Indoor Night Vision Dome Camera. Whether you're outfitting an office, warehouse, store, or restaurant, Linksys network cameras provide superior security, surveillance, and supervision.**

- Large, 5MP sensor provides superior video quality.
- Night vision, motion detection, and alarm/event notification help your business stay alert around the clock.
- Wide-angle view and wide dynamic range (WDR) available with a firmware upgrade.
- Complies with Open Network Video Interface Forum (ONVIF) core specifications, versions 1.0 and 2.0.
- True day/night functionality with removable infrared-cut filter.
- Free Video Surveillance Manager software with user, profile, and event management capabilities.

## Linksys 1080p 3MP Indoor Night Vision Dome Camera

### Specifications

Imaging	
Sensor	5 Megapixel CMOS
Maximum Image Resolution	2048 x 1536, 3MP
Video	
Maximum Frame Rate	18 fps @ 2048 x 1536 30 fps @ 1920 x 1080 30 fps @ 1280 x 720
Image Compression	H.264/MJPEG/MPEG4
Bitrate Control	Variable Bitrate and Constant Bitrate
Lens	
Fixed/Vari-focal	Fixed Lens
Iris Control	Fixed Iris
Focal Length	f = 4 mm
Focal Ratio	F1.6
Viewing Angle	Horizontal: 62° Vertical: 34°
Minimum Illumination	0 lux (IR On, B/W) 0.5 lux (IR Off, Color)
IR Illuminator	
Mechanical IR-Cut	Y
Infrared LED	12 pcs
Wavelength	850 nm
Distance (IR Distance)	15 m
Audio	
Compression	G.711/AMR
Audio Streaming	2-Way Audio
Audio Input	Y
Audio Output	Y
Compliance Information	
FCC/IC	FCC/IC Class A
CE	CE Class A
Interface	
Ethernet	100Base-T
DI/DO	Y
SD/SDHC Card Slot	Y
Power Supply	
Power over Ethernet	IEEE 802.3af
Maximum Power Consumption	< 6W
Environment	
Operating Temperature	0°C ~ 50°C
Operating Humidity	10% to 80% Relative Humidity and Non-Condensing
Storage Temperature	-20°C to 60°C
Storage Humidity	5% to 90% Non-Condensing
Dimensions	
Unit Weight	0.58 kg